HSF

NOTES:
Current Rating: 1.0AMP A2
Contact Resistance: 20mΩ Max
Withstand Voltage: 500V AC/DC
Insulation Resistance: 1000MΩ Min
Operation Temperature: −40℃ to +105℃

Contact Material:Phosphor Bronze
Contact plating:Sn over Ni
Insulator Material:LCP+30%G.F UL94V-0



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)







Section A−A

Ordering Information

3901-XX MS XX D W B X 1

No.of Pins		Contact Plating	Insulator	Color	Packing
04	16	SM=Matte Tin	D=LCP	B=Black	T=Tube
06	18	SN=Tin			
08	20				
10	22				
12	24				
14	26				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A2	2013/12/26	Modify the drawing A2	------
A1	2013/08/16	Modify the drawing A1	------
A0	2012/11/01	NEW	------

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

DRAW	JYHuang	DATE	2013/12/26
CHECK		DATE	
APPROVE		DATE	

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

PART NO. 3901-XXMSXXDWBX1

TITLE: 1.27mm Picoflex Header 180° With Peg

Customer NO.

WCON
Http: www.wcon.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com